

Office: 780-438-5930 Fax: 780-438-5707 info@afdpetroleum.com afdpetroleum.com

# **Safety Data Sheet**

Rev. Date: 1/05/2017

#### 1. PRODUCT AND COMPANY IDENTIFICATION

# **AWARD Winter Supreme Moly**

Grease

Heavy Duty Petroleum Lubricant

Product Code: G922

Universal Lubricants, A PetroChoice Company

2824 N Ohio Street Wichita, Kansas 67219

Website: www.universallubes.com

1-800-444-6457 Telephone 1-316-832-3627 Product Information telephone

1-800-424-9300 US, Canada, Puerto Rico, Virgin Isl.- Emergency

telephone(CHEMTREC)

+1-703-527-3887 International / Maritime Emergency telephone (CHEMTREC)

#### 2. HAZARDS IDENTIFICATION

#### **OSHA/HCS Status:**

While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of this product.

Physical Hazards: Not classified

Health Hazards: Not classified

**Environmental Hazards: Not classified** 

Signal Word: No signal word

Hazard Statement: No known significant effects or critical hazards

**GHS Symbol:** *No Symbol* 



Canada T6P 1L7

Office: 780-438-5930 Fax: 780-438-5707 info@afdpetroleum.com afdpetroleum.com

# **Precautionary Statements**

**General:** Read label before use. Keep out of reach of children. If medical

advice is needed, have product information at hand.

**Prevention:** Not applicable

**Response:** Not applicable

**Storage:** Not applicable

**Disposal:** Not applicable

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms: Heavy Duty Petroleum Lubricant, Grease

Formula: Mixture

Molecular Weight: Variable

Component	CAS Number	Concentration
Base Lubricating Oils Mixture		70-90 %
Calcium Sulfonate	Trade Secret	10-30 %
Molybdenum Disulfide	Trade Secret	1-5 %

#### 4. FIRST AID MEASURES

#### **Eyes**

Immediately flush eyes with large amounts of fresh water and continue flushing until irritation subsides. Seek medical attention.

#### **Inhalation**

If breathing difficulty exists, remove individual away from exposure and into fresh air. Seek medical attention

#### Skin

Remove contaminated clothing. Wash contaminated area repeatedly with soap and water. Seek medical attention for persistent irritation.

#### **Ingestion**

Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.



Office: 780-438-5930 Fax: 780-438-5707 info@afdpetroleum.com afdpetroleum.com

#### 5. FIREFIGHTING MEASURES

# Suitable extinguishing media

Use dry chemical, foam, carbon dioxide (CO<sub>2</sub>) or water spray or water fog.

# **Specific hazards from combustion**

Carbon monoxide, carbon dioxide and other oxides may be products of combustion.

# Special protective equipment for fire-fighters

Wear full firefighting turn-out gear (full bunker gear), and respiratory protection (SCBA). Cool fire exposed containers with water spray and avoid spreading burning material with water used for cooling purposes.

#### **6. ACCIDENTAL RELEASE MEASURES**

# **Personal precautions and Protective equipment**

Personal Protection, see section 8. Any individual not wearing protective equipment should not enter spill or contaminated area until all clean-up has been completed.

# **Emergency procedures**

For personal emergency procedures see section 4. For fire emergency procedures see section 5. Contain spilled oil liquid if possible without posing any risk or personal injury.

#### **Environmental precautions**

Prevent spreading over a wide area. Contain spill immediately. Contact appropriate authorities of spill. Do not allow spill to enter sewer system, drains of any kind, surface water or water courses. Avoid flushing to such areas as well

# Methods and materials for containment and cleaning up

Soak up or absorb with appropriate inert materials such as, sand, clay, silica gel, acid binder, universal binder, sawdust, paper fiber etc. Large spills may be picked up using vacuum pumps, shovels, buckets or other means of transfer and placed into drums or any other approved and suitable containers.



Office: 780-438-5930 Fax: 780-438-5707 info@afdpetroleum.com afdpetroleum.com

#### 7. HANDLING AND STORAGE

# Precautions for safe handling

#### **Conditions for safe storage**

Store in only approved and marked containers. Keep containers closed when not in use and during transportation. Keep containers away from flame or other ignition sources.

# **Incompatibilities**

May react strong with oxidizing agents, such as hydrogen peroxide, bromine, and chromic acid.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

# **Occupational exposure limits**

Ingredient name	Exposure limits
2-Methylpentane-2,4-diol	ACGIH TLV (United States, 3/2015). C: 121 mg/m³ C: 25 ppm NIOSH REL (United States, 10/2013). CEIL: 125 mg/m³ CEIL: 25 ppm OSHA PEL 1989 (United States, 3/1989). CEIL: 25 ppm CEIL: 125 mg/m³

#### Respiratory protection

If vapor mist is generated when the material is heated or handled, use approved respiratory protection. All respirators must be NIOSH certified. Fit testing may be required before use. Do not use compressed oxygen in hydrocarbon atmospheres. Adequate ventilation in accordance with good engineering practices must be provided to maintain concentrations below the specified exposure or flammable limits.

# **Hand protection**

If handling hot material, use proper insulated gloves.

### Eye protection

Not required under normal conditions of use. If material is handled such that it could be splashed or misted into eyes, wear plastic face shield or splash resistant safety goggles or glasses with side shields.



Office: 780-438-5930 Fax: 780-438-5707 info@afdpetroleum.com afdpetroleum.com

# Skin and body protection

Use impervious clothing (boots, gloves, aprons, bibs, etc.) over parts of the body subject to exposure. If handling hot material, use insulated protective clothing. Contact your facility safety department or safety supplier to determine the proper protective equipment for your use.

# **Hygiene measures**

Do not use contaminated clothing, launder clothing before reuse. Properly dispose of contaminated clothing or articles that cannot be laundered such as leather gloves, boots, etc. Wash contaminated areas of the body which may have been exposed with soap and water. Wash thoroughly before handling food and beverages. Food and beverage consumption should be avoided in work areas where hydrocarbons are present.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance:** Semi-solid, Black

Physical state: Solid

Odor: Mild, bland petroleum odor

Specific gravity ( $H_2O=1$ ): 0.9500

Melting point/freezing point: No data available

Initial boiling point and boiling range: No data available

Flash point (C.O.C): 224°C, (435°F)

**Upper/lower flammability or explosive limits:** No data available

**Vapor pressure:** Less than 0.01 @20°C

**Solubility in water:** Negligible, less than 0.1%

Percent volatile: Negligible

Vapor density (air=1): Greater than 5

**Evaporation rate:** Less than 0.01 (butyl acetate=1)



Office: 780-438-5930 Fax: 780-438-5707 info@afdpetroleum.com afdpetroleum.com

#### 10. STABILITY AND REACTIVITY

**Reactivity:** No data available.

Chemical stability: Stable under normal temperatures and pressures.

Possibility of hazardous reactions: Product will not undergo hazardous

polymerization.

Conditions to avoid: Heat, open flames, oxidizing materials and mist.

**Incompatible materials:** Strong oxidizing agents.

Hazardous decomposition products: Carbon monoxide, carbon dioxide and other

oxides may be generated as products of

combustion.

# 11. TOXICOLOGICAL INFORMATION

# Acute oral toxicity:

Product/ingredient name	Result	Species	Dose	Exposure
2-Methylpentane-2,4-diol	LD50 Oral	Rat	3700 mg/kg	-

### Acute dermal toxicity:

<b>Product/ingredient name</b>	Result	Species	Score	Exposure	Observation
	Skin - Mild irritant Skin - Moderate irritant	Rabbit Rabbit	-	465 mg 24 hours 500 mg	-

#### 12. ECOLOGICAL INFORMATION

## **Toxicity:**

Product/ingredient name	Result	Species	Exposure
2-Methylpentane-2,4-diol	Acute EC50 2800000 to 3200000 μg/L Fresh water	Crustaceans - Ceriodaphnia reticulata - Larvae	48 hours
		:	48 hours 96 hours



Office: 780-438-5930 Fax: 780-438-5707 info@afdpetroleum.com afdpetroleum.com

Persistence and degradability: No data available

# **Bioaccumulative potential:**

Product/ingredient name	LogPow	BCF	Potential
2-Methylpentane-2,4-diol	0.58	-	low
Polysulfides, di-tert-dodecyl	>6.2		high

### **Mobility in soil:**

Soil/water partition coefficient (Koc): Not available.

**Other adverse effects:** No known significant effects or critical hazards.

#### **13. DISPOSAL CONSIDERATIONS**

### **Waste Disposal methods**

All disposals must comply with federal, state and local regulations. Spilled or discarded material may be a regulated waste. Refer to state and local regulations. If other material was used during cleanup efforts the resultant mixture may be regulated.

#### TRANSPORT INFORMATION 14.

**U.S. DOT Road/Rail/Waterways:** Not dangerous/hazardous goods

**Transport Canada Road/Rail/Waterways:** Not dangerous/hazardous goods

#### **15.** REGULATORY INFORMATION

**U.S. Federal regulations:** United States inventory (TSCA 8b): All

components are listed or exempted.

Clean Air Act Section 112:

Not listed

(b) Hazardous Air

**Pollutants (HAPs)** 

**Clean Air Act Section 602:** 

Not listed

Not listed

**Class I Substances** 

Clean Air Act Section 602:

Class II Substances



Distributed by

Canada T6P 1L7

AFD Petroleum Ltd. 1444 - 78 Avenue NW Edmonton, AB Office: 780-438-5930 Fax: 780-438-5707 info@afdpetroleum.com afdpetroleum.com

**DEA List I Chemicals:** Not listed

(Precursor Chemicals)

**DEA List II Chemicals:** (Essential Chemicals)

Not listed

SARA 302/304

# **Composition/information on ingredients**

		SARA 302 TPQ SARA 304 RQ		SARA 302 TPQ		
Name	%	EHS	(lbs)	(gallons)	(lbs)	(gallons)
Ethylene oxide	0 - 0.01	Yes.	1000	-	10	-

**SARA 304 RQ:** 555555.6 lbs / 252222.2 kg

**SARA 311/312** 

**Classification:** Not applicable.

# **Composition/information on ingredients**

Name	%	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
2-Methylpentane-2,4-diol	1 - 5	No.	No.	No.	Yes.	No.

## **SARA 3136**

No products were found.

#### State Regulations

**Massachusetts:** The following components are listed: 2-

Methylpentane-2, 4-diol; Molybdenum disulphide

**New York:** None of the components are listed.

**New Jersey:** The following components are listed: 2-

Methylpentane-2, 4-diol; Distillates (petroleum),

hydrotreated heavy paraffinic

**Pennsylvania:** The following components are listed: 2-

Methylpentane-2, 4-diol



Canada T6P 1L7

Office: 780-438-5930 Fax: 780-438-5707 info@afdpetroleum.com afdpetroleum.com

# California Prop. 65

**WARNING:** This product contains less than 0.1% of a chemical known to the State

of California to cause cancer.

**WARNING:** This product contains less than 1% of a chemical known to the State of

California to cause birth defects or other reproductive harm.

Ingredient name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
Ethylene oxide	Yes.	Yes.	Yes.	Yes.

### **NFPA Hazard Classification**

Health: 0 Flammability: 1 Reactivity: 0

#### **HMIS Classification**

Health: 0 Flammability 1 Physical Hazards: 0 Personal Protection: B



HEALTH	0
FLAMMABILITY	1
PHYSICAL HAZARD	0
PERSONAL PROTECTION	В

#### 16. OTHER INFORMATION

The information accumulated herein is believed to be accurate. However, neither Universal Lubricants, nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information provided herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot quarantee that these are the only hazards which exist.