



# AWARD Automatic Transmission Fluid DEXRON® VI

PREMIUM AUTOMATIC TRANSMISSION FLUID

## PRODUCT LINE

AWARD Lubricants Automatic Transmission Fluid (ATF) DEXRON® VI is a next generation fluid approved for use in passenger car and light truck automatic transmissions that require a General Motors DEXRON® VI or earlier generation DEXRON® fluid.

## APPLICATIONS

AWARD ATF DEXRON® VI is particularly recommended for use in new GM 6-speed automatic transmissions and is fully backwards compatible with older GM automatic transmissions. AWARD ATF DEXRON® VI is recommended for service fill in passenger cars and light trucks that require a GM DEXRON® transmission fluid. It also may be used in industrial and mobile hydraulic systems operating over a wide temperature range.

**Suitable for use in all applicable GM automatic transmissions. Not recommended for transmissions requiring MERCON of Ford Type F ATF.**

## PERFORMANCE BENEFITS

- Improved oxidation stability
- Superior shear stability
- Enhanced friction durability
- Foam resistance


### Available In These Sizes



Pails



Drums



Totes



1.800.926.FUEL (3835) • [AFDPetroleum.com](http://AFDPetroleum.com)

P: 780.438.5930 • F: 780.438.5707 • 1444 78 Avenue NW Edmonton, AB, Canada • T6P 1L7



## TYPICAL PROPERTIES

	DEXRON® VI	ASTM TEST METHOD
Viscosity @ -40°C, cP	10,000	D2983
Viscosity @ 40°C, cSt	29.00	D445
Viscosity @ 100°C, cSt	5.95	D445
Viscosity Index	155	D2270
Flash Point, COC, °C (°F)	216 (420)	D92
Pour Point, °C (°F)	-51 (-60)	D97
Color	RED	Visual
Gravity, °API	36.0	D287
Zinc, ppm	< 20	
DEXRON® VI Tests:		
Oxidation	Pass	
Bench Tests	Pass	
Band and Plate Friction	Pass	
Elastomer Test	Pass	

## PERFORMANCE SUMMARY

SPECIFICATIONS AND APPROVALS	AWARD ATF DEXRON® VI
General Motors – DEXRON® VI	Yes
GM License Number – J-60157	Yes

### Health & Safety

This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

### SDS

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed.

MSDS can be found at: <https://www.afdpetroleum.com/safety>

*\*Always consult with original equipment manufacturer's recommendations for specific performance and viscosity requirements.*

*\*Extending drain intervals should always be undertaken in conjunction with a regular oil analysis program.*

*\*Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations.*

*Product formulations are subject to change without notice.*